

HIGH CURRENT STAINLESS STEEL 316 PUSHBUTTON



- Designed for Marine and onshore applications
- 19mm cutout diameter
- 50 different sticker symbols available
- Different LED colors available
- Stainless Steel 316 housing
- Momentary Off - (On) – Latching Off – On
- IP67 certified
- IP65 Connector available
- CE-certified

Part number: PF19D-20(SS) / PF22D-20(SS)

Specifications

Max. current:	20A
Supply Voltage:	3.3V / 5V /12V / 24V
Mechanical life:	50.000 cycles
Contact resistance:	50 mΩ
Insulation resistance:	1000MΩ
Operating temperature:	-20 to +55 C
Button travel:	2.50mm
Protection:	IP67
Actuation force:	4Nm
Output:	NO (Normally Open)
Mounting Nut torque:	5 – 14NM
Type:	Latching or Momentary
Material:	Stainless Steel 316
LED State for output indication:	
1- Always on	
2- Only on when pressed	

Applications

Marine:	Exterior switch panels Interior control panels Offshore applications
Industrial:	Farming equipment Heavy machinery
On-shore	RV power distribution panels Car switch panels Kiosks Security devices

Part number configurator

Connector



Y – Yes
N - No

Function



M – Momentary
L - Latching

LED style



W – White
Y- Yellow
B – Blue
G- Green
R – Red

HIGH CURRENT STAINLESS STEEL 316 PUSHBUTTON

