## NOR TIDE

## **Pushbuttons Switches** For the marine industry

Mount diameter: Voltage rating: Max Current: Mechanical life:"

cycles LED life: IP rating: Operating temp:

**Button travel:** Contact material:

**Actuator force:** Max panel thickness: 19mm – 22mm 12VDC / 24VDC 5A / 10A / 20A >100.000

40.000 hours IP67 -10°C -+ 45°C

2.8mm Silver 3-5N 1-10mm

**Body Material Optional** 





#### **Performance series** PF19D/22D



#### **LED Type Optional**









#### **Switch Function**

Item NO.	Fuction	Non Press	1st Press	2nd Press	3rd Press	Switch Rating	Feature
PF19D-20A PF22D-20A	OFF-ON	OFF	ON	OFF	ON	20A, 250VAC DC	Standard switch
PF19D-10 PF22D-10	OFF-ON	OFF	ON	OFF	ON	5A/10A/15A/20A, 250VAC DC	Overload protection
PF19D-20 PF22D-20	OFF-ON	OFF	ON	OFF	ON	20A, 12VDC	Bi-COLOR LED
PF19D-30 PF22D-30	OFF- ON-ON	ALL OFF	Load 1 ON Load 2 OFF	Load 1 OFF, Load 2 ON	ALL OFF	10A (5A/Per Load), 12VDC	Two channel
PF19D-40 PF22D-40	OFF-ON-ON (NAV-ANC)	ALL OFF	Load 1 ON Load 2 ON	Load 1 OFF, Load 2 ON	ALL OFF	10A(5A/Per Load), 12VDC	Two channel (NAV-ANC)





#### PF19D-00 / PF22D-00

20A ON OFF Push Button Switch


#### Feature

- ◆ High current (20amp) push button switch;
- ◆ IP67 waterproof;
- ◆ 316L stainless steel body protection from Salt spray;
- Special harness and waterproof rings.




#### **Specification**

Item NO.		PF19D-00- <b>M</b>	PF19D-00- <b>L</b>	PF22D-00- <b>M</b>	PF22D-00- <b>L</b>		
Hole size		19MM(3/4")	19MM(3/4")	22mm ( 7/8" )	22mm ( 7/8" )		
Operation		<b>M</b> omentary	Latching	<b>M</b> omentary	Latching		
Switch Rat	ing	20A/250VAC DC					
Body Material		316 Stainless Steel or Bla	ack Anodize Aluminium				
	TYPE	Ring,Power,Marine Logo series,Special sticker, Customizable.					
LED	Volt	3V,6V,12V,24V,					
LLD	Color	RED,BLUE,GREEN,YELLO	DW,WHITE,BI-COLOR				
	Life	More than 40,000 hours					
Harness	Material	Flame retardant material					
	Wire Size& Color	22AWG (LED POWER,RED & BLACK) 16AWG (SWITCH NO-NO,BLUE)					
	Wire Length	ABOUT 28CM,Customizab	ABOUT 28CM,Customizable				



#### Wiring



#### LED output indicator

Switch OFF Light OFF Pressing the pushbutton

Switch ON

ON Light ON

# + POWER NO NO NO

#### **LED Always ON**

Switch ON

Switch OFF
Pressing the pushbutton

Light ON

Light ON





#### PF19D-10 / LA22D-10

## Overload Protection Push E

#### Feature

- Overload protection push button switch;
- ◆ 5A/10A/15A/20A switch rating
- ◆ 316L stainless steel body protection from Salt spray;
- ◆ IP67 Waterproof.



#### Specification

		PF19D-10/5A PF22D-10/5A	PF19D-10/10A PF22D-10/10A	PF19D-10/15A PF22D-10/15A	PF19D-10/20A PF22D-10/20A		
Switch Ra	ating	5A,250VACDC	10A,250VACDC	15A,250VACDC	20A,250VACDC		
Base colo	r	Orange	Red	Blue	Yellow	×	
Hole size		19MM(3/4") 22mm ( 7/8")	19MM(3/4") 22mm ( 7/8")	19MM(3/4") 22mm ( 7/8")	19MM(3/4") 22mm ( 7/8")	000 000 000 000 000 000 000 000 000 00	
Material	Body	316 Stainless Stee	(SS) or Black Anodize	Aluminium (AB)		M19X1	
	Base	PBT	РВТ				
LED	Туре	Ring,Power,Marine	Ring,Power,Marine Logo series,Special sticker, Customizable.				
	Volt	12V,24V	12V,24V				
	Color	RED,BLUE,GREEN	,YELLOW,WHITE,BI-CO	LOR			
	Life	More than 40,000 h	nours				
Wire	Switch NO	16 AWG,Brown wire(Fuse)					
	Switch NO	14awg,Red wire		LED +	SWITCH NO	100±10	
	LED +	22awg,Red wire		SWITCH NO	LED -	<u> </u>	
	LED -	22awg,Black Wire					

#### **Function**

SWITCH RATING	CURRENT * 1. 2	CURRENT * 1.5	CURRENT * 2	When the current returns to normal, the heat dissipates	
	Switch can run for a long time	Switch will be disconnected within 150(270) seconds	Switch will be disconnected within 5 seconds		
5A	6A	7.5A (270seconds)	10A	Switch	
10A	12A	15A	20A	automatically returns to normal	
15A	18A	22.5	30A	operation.	
20A	24A	30A	34A		





#### PF19D-20 / PF22D-20

Bi-color Push Button Switch

#### Feature


- ◆ Dual LED color (Bi-color) push button switch;
- 20A High current, IP67 Waterproof.;
- Semi-mechanical push button switch, integrated circuit board;
- 316L stainless steel body protection from Salt spray;



#### Specification

Item No	0.	PF19D-20 PF22D-20		<b>\</b>
Hole siz	ze	19MM(3/4")	22MM(7/8")	Ø15.4
Operati	on	Latching or Momentary	Latching or Momentary	
Switch	Rating	20A/12VAC DC		m , ø21.8 , ×
Materia	I	Body: 316 Stainless Steel or Black Base: PA66-GF15 Sealing Filler: Epoxy Resin	Ø21.8 Ø Ø17 III	
	TYPE	Ring,Power,Marine Logo series, All-	M19X1	
LED	Volt	12V DC	86±1.0	
	Color	Bi-Color: Green&Blue, Red&Blue, Re	d&Green etc. (customizable)	
	Life	More than 40,000 hours	+	
Wire	Red Wire (14AWG)	INPUT "+",		9
	Blue Wire (14AWG)	OUTPUT "+"	OUTPUT + (Control LED)	150±10
	Black Wire (18AWG)	Common "-"	COMMON - OUTPUT +	
	Green Wire (18AWG)	INPUT "+",Control LED light on of off,when switch is OFF		, 0000

#### Function








PF19D-30 / PF22D-30


## Two Channel Push Butte

#### - .

- Two channel / Dual output push button switch;
- 10A maximum current, each channel 5A.;
- IP67 Waterproof;
- 316L stainless steel body protection from Salt spray;
- ◆ The color of the LED can be customized

#### Specification





#### **Functior**

WIRING	LED color Customizable Take the PF19D-30GRB, PF19D-30NRB For example						
	MODEL	PF19D-30	GRB		PF19D-30	NRB	
	STATE	Load 1	Load 2	LED	Load 1	Load 2	LED
+ (LOAD1) (LOAD2)	Non press	OFF	OFF	Green	OFF	OFF	Non
12/	1st press	ON	OFF	Red	ON	OFF	Red
	2nd press	OFF	ON	Blue	OFF	ON	Blue
	3rd press	OFF	OFF	Green	OFF	OFF	Non





PF19D-40 / PF22D-40

NAV/ANC Push Button Switch

#### Feature


- ◆ Two channel (NAV/ANC) push button switch;
- ◆ 10A current, each channel 5A.;
- ◆ IP67 Waterproof;
- 316L stainless steel body protection from Salt spray;
- ◆ The color of the LED can be customized.



#### Specification

Item No	0.	PF19D-40	PF22D-40	P.	
Hole si	ze	19MM(3/4") 22MM(7/8")		Ø15.4	
Operation		1ST press, Load 1 on,Load 2 on; 2ND press, Load 1 off,Load 2on; 3RD press, Load 1& Load 2 all off			
Switch	Rating	10A/12VAC DC,each channel 5A	∞  <del>  Ø21.8</del>		
Material		Body: 316 Stainless Steel or Black Base: PA66-GF15 Sealing Filler: Epoxy Resin	M19X1		
	TYPE	Ring,Power,Marine Logo series,All-t	86±1.0		
	Volt	12V DC	12V DC		
LED	Color	RED&BLUE (Other bi-color,tri-color			
	Life More than 40,000 hours			<u> </u>	
Wire	Red Wire (16AWG)	INPUT "+",			
	Black Wire (16AWG)	Common "-"	IN PUT + OUTPUT + (Channel 1)	150±10	
	Blue Wire (16AWG)	Channel 1 OUT PUT "+"	COMMON - OUTPUT + (Channel 2)		
	Brown Wire (16AWG)	Channel 2 OUT PUT "+"		1 1 1 1 1	

#### Function





## **OFF-ON**

#### PF19D-50

#### Backlit pushbutton with symbol


- ◆ High current (20amp) push button switch;
- IP65 waterproof;
- ◆ 304L stainless steel body protection from Salt spray;
- Special harness and waterproof rings.
- ♦ 50 different symbol stickers available
- ◆ LED color: Blue, Red, White




Item NO.		PF19D-50- <b>M</b>	PF19D-50- <b>L</b>			
Hole size		19MM(3/4")	19MM(3/4")			
Operation		Momentary	Latching			
Switch Ra	ting	20A/12VDC DC				
Body Mate	rial	304 Stainless Steel				
	TYPE	Ring,Power,Marine Logo	Ring,Power,Marine Logo series,Special sticker, Customizable.			
LED	Volt	12V				
LLD	Color	RED,BLUE,WHITE				
	Life	More than 40,000 hours				
Harness	Material	Flame retardant material				
	Wire Size& Color	22AWG (LED POWER,RED & BLACK) 16AWG (SWITCH NO-NO,BLUE)				
	Wire Length None					











#### **LED** output indicator

Switch OFF Light OFF

Pressing the pushbutton

Switch ON Light ON

#### **LED Always ON**

Switch OFF

Pressing the pushbutton

Switch ON Light ON

Light ON



## **ON-OFF**


#### PF19D-60

#### Stainless steel pushbutton

- ◆ High current (20amp) push button switch;
- ◆ IP67 waterproof;
- ◆ 316L stainless steel body protection from Salt spray;
- Special harness and waterproof rings.
- imbedded cable (60 cm cable length)
- ◆ LED color: Blue
- Max. panel thickness: 1mm 8mm




Ite Spe	cification	PF19D-60- <b>M</b> PF19D-60- <b>L</b>				
Hole size		19MM(3/4")	19MM(3/4")			
Operation		<b>M</b> omentary	Latching			
Switch Rat	ing	20A/12/24VDC				
Body Material		316 Stainless Steel				
	TYPE	Ring,Power,Marine Logo series,Special sticker, Customizable.				
LED	Volt	12V/24V				
LLD	Color	BLUE				
	Life	More than 40,000 hours				
Harness	Material	Flame retardant material				
	Wire Size& Color	22AWG (LED POWER,RED & BLACK) 16AWG (SWITCH NO-NO,BLUE)				
	Wire Length	None	None			



#### **LED** output indicator

Switch OFF Light OFF Pressing the pushbutton Switch ON

Light ON



#### **LED Always ON**

Switch OFF Pressing the pushbutton Switch ON

Light ON

Light ON



## Buzzer

### PF19D-70

#### 12V or 24V buzzer alarm

- ◆ High current (20amp) push button switch;
- ◆ IP50;
- ◆ 304L stainless steel body
- Special harness and waterproof rings.
- imbedded cable (60 cm cable length)
- ♦ LED color: RED
- Max. panel thickness: 1mm 8mm



Ite Spe	cification	PF19D-60- <b>M</b>				
Hole size		19MM(3/4")				
Operation		Intermittent beep (80 dB)				
Current rati	ing	<3A				
Body Mate	rial	304 Stainless Steel				
	TYPE	Intermittent beep				
LED	Volt	12V or 24V				
LLD	Color	RED				
	Life	More than 40,000 hours				
Harness	Material	Flame retardant material				
	Wire Size& Color	None				
	Wire Length	None				

	PFxxD-20A	PFxxD-10	PFxxD-20	PFxxD-30	PFxxD-40	PFxxD-50	PFxxD-60	PFxxD-70
19mm	€20,00	€25,00	€20,00	€37,00	€37,00	19,00	23,00	35,00
22mm	€22,00	€27,00	€22,00	€39,00	€39,00	-	-	-

#### Summarv

Julililaiy	
PFxxD-00	Heavy duty pushbutton
PFxxD-10	Overload protection pushbutton switch
PFxxD-20	Pushbutton DUAL LED switch
PFxxD-30	Two channel pushbutton switch
PFxxD-40	NAV/ANC pushbutton switch
PFxxD-50	Backlit pushbutton switch
PFxxD-60	Stainless Steel pushbutton switch

12V or 24V buzzer alarm

## Need support?

Sales@nortidemarine.com

PFxxD-70





www.nortidemarine.com